

**DIRECT THERMAL AND
THERMAL TRANSFER
PRINTER**

EasyCoder™ **C4**

Benefits:

- Comes complete with **Connect & Print™** accessories for easy set up. Nothing else to buy.
- Easy to set up, use and own. Animated instruction sequences on CD, and easy-to-read QuickGuide ensures minimal time to first printed label.
- Sturdy printer at a competitive price
- New, unique double clam shell design offers easy drop-in loading of paper and ribbon supplies
- Dual print technology ensures ability to print on most label types
- Dispensing with Label-Taken sensor is standard
- Attractive design and compact size
- Easily replaceable QuickMount printhead. No need for any tools.



The EasyCoder C4 is the perfect printer for the inexperienced or busy user. Intermec's new Connect & Print™ concept makes setting up and printing a quick and easy task.

Everything is included in the low price: software, drivers, cables, and labels. The printer comes complete with LabelShop® START — Intermec's label design software — and InterDriver™ Windows™ Driver with ActiveX® Controls. Intermec's InterDriver™ with ActiveX® enables the user to easily print bar code labels from Windows applications, including Microsoft® Office™ and other popular programs.

The printer's compact size, sturdiness, and silent operation make it ideal for a variety of applications.

The EasyCoder C4 prints faster and with better quality than competing printers in its price range, and includes dual print technology for printing on various label types; both Direct Thermal and Thermal Transfer.

The new, unique double clam shell design makes it extremely easy to load supplies with the simple drop-in method.

Exchanging label and ribbon rolls can be done in no time.

The RS232 and Centronics™ interfaces are standard, which allows easy communication with the printer. Firmware can easily be upgraded thanks to the Flash memory.

The EasyCoder C4 printer comes with standard features like Peel-off operation with Label-Taken sensor and Black Mark sensor.

Among its optional features are:

- Flash memory cartridge
- SRAM memory cartridge
- Serial cable

The new EasyCoder C4 printer is compatible with all EasyCoder 91 and EasyCoder 7422 applications, so adding the new EasyCoder C4 is simple.

With all its built-in benefits, the EasyCoder C4 is really a smart choice that offers excellent value for an affordable price.

EasyCoder™ C4

General Description

A very compact Direct Thermal or Thermal Transfer/Direct Thermal printer for self-adhesive labels, non-adhesive tags, or continuous paper strip. Tear-off or Peel-off operation with Label-Taken Sensor. Internal paper roll or external fan-fold supply. Black Mark Sensor.

Model

EasyCoder™ C4 Direct Thermal
EasyCoder™ C4 Thermal Transfer/
Direct Thermal

Physical Characteristics

Length: 257 mm (10.23 in)
Height: 167 mm (6.58 in)
Width: 230 mm (9.06 in)
Weight: 2.3 kg (5.07 lbs)

Print Specifications

Label Size –

Max. Width: 118 mm (4.65 in)
Max. Length: 200 mm (8 in) with 256 Kb SRAM

Print Direction: Prints text, bar codes and dot-addressable graphics in all four directions

Print Resolution: 8 dots/mm (203 dpi)

Print Width: Max. 104 mm (4.1 in)

Printing Speed: Selectable, 30, 40, 50 or 75 mm/sec (1.2, 1.6, 2 or 3 in/sec)

Media Specifications

Label Roll –

Max. Diameter: 125 mm (5 in)
Core Diameter: Min. 25.4 mm (1 in)
Max. 38.1 mm (1.5 in)

Paper Width: Max. 118.0 mm (4.65 in)

Min. 25.0 mm (1 in)

Label Length: Min. 6.35 mm (0.25 in)

Ribbon Roll –

Max. length: 91 m (298 feet)

Labels: A wide selection of stock and custom size labels are available.

Ribbons: Intermec transfer ribbons only (wax, hybrid, and resin) in widths of 33, 60, 63.5, 83.5, 89, and 110 mm (1.33, 2.36, 3.29, 3.5, and 4.33 in) centered on 110 mm (4.33 in) wide cardboard cores. Core inner diameter 13 mm (0.5 in) with notches. Max. ribbon roll diameter 41 mm (1.6 in).

Connect & Print™

Intermec's program offering "everything in the box". The printer comes with all included: software, drivers, cables, labels, a handy QuickGuide to facilitate getting started, and a PrinterCompanion CD with label design program, Windows™ driver and documentation.

Software

Comes standard with Intermec's LabelShop® START label design software, and InterDriver™ with ActiveX® Controls for Microsoft™ Windows™.

Supports: Windows 3X, 95, 98, and NT 4.0

Characters/Fonts

5 resident alphanumeric fonts that are expandable 8 times horizontally and 9 times vertically. Printing of graphics and symbols is also possible. Downloading of additional fonts is possible via "Font Downloader" in the LabelShop START program.

Bar Code Symbolologies

All major 1-dimensional bar code symbolologies are available, plus two 2-dimensional codes: MaxiCode and PDF417.

Environment

+5° to +40°C (+40° to +104°F).

Humidity

10–90% RH non-condensing.

Power Supply

Separate power supply unit –
Input: 100–240 V AC/50–60 Hz, 1.9 A
Output: 24 V DC, 3.0 A

Memory

Standard: 200 kB Flash
170 kB SRAM
Optional: 1 MB Flash or
256 kB SRAM

Interface

Standard: RS-232C, Centronics

Protocol

XON/XOFF, DSR/CTS.

Operator Control

One multi-color LED indicator lamp and one Print/Feed key

Regulatory Approvals

CE Class A Standards

Options

Flash memory cartridge,
SRAM memory cartridge,
Serial communication cable

Internet • www.intermec.com **Sales** • 800.347.2636 (toll free in N.A.), 425.348.2726 **Service and Support** • 800.755.5505 (toll free in N.A.), 425.356.1799

North America
Corporate Headquarters • 6001 36th Avenue West, Everett, Washington 98203, tel: 425.348.2600, fax: 425.355.9551
Systems & Solutions • 550 2nd Street S.E., Cedar Rapids, Iowa 52401, tel: 319.369.3100, fax: 319.369.3453
Media Supplies • 9290 Le Saint Drive, Fairfield, Ohio 45014, tel: 513.874.5882, fax: 513.874.8487

Europe/Middle East & Africa
Headquarters • Sovereign House, Vastern Road, Reading, Berkshire RG1 8BT, United Kingdom, tel: +44.118.987.9400, fax: +44.118.987.9401
Gothenburg • Idrottsvägen 10, P.O. Box 123, SE-431 22 Mölndal, Sweden, tel: +46.31.869500, fax: +46.31.869595

Asian Pacific/Latin America
Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, Hong Kong, tel: 852.2574.9777, fax: 852.2574.9725
Singapore • 25-16 International Plaza, 10 Anson Road, 079903, tel: 65.324.8391, fax: 65.324.8393
Australia • 15 Stamford Road, Oakleigh, Victoria 3166, tel: 61.3.9563.0000, fax: 61.3.9563.4000
South America and Mexico • 2572 White Road, Irvine, California 92614, tel: 949.975.1905, fax: 949.975.1913

Worldwide Fax Document Retrieval Service • 800.755.5505 (North America Only) • tel: 650.556.8447

Copyright © 2000 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 609122-01A 10/00

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.